

## MISTO ARIA - MISURE UGELLI DISPONIBILI



### UGELLO MIX

TTUXXX

Esempio: Per un ugello con foro .011mm e angolo 30° ordinare TTU311

Misure disponibili nella tabella sotto. Su richiesta ulteriori misure

| IN    | MM        | Angolo | .007 | .009 | .011 | .013 | .015 | .017 | .019 | .021 |
|-------|-----------|--------|------|------|------|------|------|------|------|------|
| 2-4   | (50-102)  | 10°    | 107  | 109  | 111  |      |      |      |      |      |
| 4-6   | (102-152) | 20°    | 207  | 209  | 211  | 213  | 215  | 217  | 219  | 221  |
| 6-8   | (152-203) | 30°    | 307  | 309  | 311  | 313  | 315  | 317  | 319  | 321  |
| 8-10  | (203-254) | 40°    |      | 409  | 411  | 413  | 415  | 417  | 419  | 421  |
| 10-12 | (254-305) | 50°    |      | 509  | 511  | 513  | 515  | 517  | 519  | 521  |
| 12-14 | (305-356) | 60°    |      | 609  | 611  | 613  | 615  | 617  | 619  | 621  |
| 14-16 | (356-406) | 70°    |      |      | 711  | 713  | 715  | 717  | 719  | 721  |
| 16-18 | (406-457) | 80°    |      |      |      |      | 815  | 817  | 819  | 821  |
| 18-20 | (457-508) | 90°    |      |      |      |      |      | 917  | 919  | 921  |



### UGELLO MIX TIPO BINKS

BNKXXX

Esempio: Per un ugello con foro .011mm e angolo 30° ordinare BNK311

Misure disponibili nella tabella sotto. Su richiesta ulteriori misure

| IN    | MM        | Angolo | .007 | .009 | .011 | .013 | .015 | .017 | .019 | .021 |
|-------|-----------|--------|------|------|------|------|------|------|------|------|
| 2-4   | (50-102)  | 10°    | 107  | 109  | 111  |      |      |      |      |      |
| 4-6   | (102-152) | 20°    | 207  | 209  | 211  | 213  | 215  | 217  | 219  | 221  |
| 6-8   | (152-203) | 30°    | 307  | 309  | 311  | 313  | 315  | 317  | 319  | 321  |
| 8-10  | (203-254) | 40°    |      | 409  | 411  | 413  | 415  | 417  | 419  | 421  |
| 10-12 | (254-305) | 50°    |      | 509  | 511  | 513  | 515  | 517  | 519  | 521  |
| 12-14 | (305-356) | 60°    |      | 609  | 611  | 613  | 615  | 617  | 619  | 621  |
| 14-16 | (356-406) | 70°    |      |      | 711  | 713  | 715  | 717  | 719  | 721  |
| 16-18 | (406-457) | 80°    |      |      |      |      | 815  | 817  | 819  | 821  |
| 18-20 | (457-508) | 90°    |      |      |      |      |      | 917  | 919  | 921  |

## MISTO ARIA - MISURE UGELLI DISPONIBILI



### UGELLO BERIZZI

BRZ4

Esempio: Per un ugello con foro .011mm e angolo 30° ordinare BRZ311

Misure disponibili nella tabella sotto. Su richiesta ulteriori misure

| IN    | MM        | Angle     | .007-03 | .009-04 | .011-06 | .013-09 | .015-12 | .017-14 | .019-18 | .021-20 |
|-------|-----------|-----------|---------|---------|---------|---------|---------|---------|---------|---------|
| 2-3   | (50-90)   | 20° - 034 | 207     | 209     | 211     | 213     |         | 217     |         |         |
| 3-5   | (90-130)  | 25° - 054 | 2507    | 2509    | 2511    | 2513    |         |         | 2519    |         |
| 5-7   | (130-170) | 30° - 074 | 307     | 309     | 311     | 313     | 315     | 317     | 319     | 321     |
| 7-8   | (170-220) | 40° - 094 |         | 409     | 411     | 413     | 415     | 417     | 419     | 421     |
| 8-10  | (220-270) | 50° - 114 |         | 509     | 511     | 513     | 515     | 517     | 519     | 521     |
| 10-11 | (270-290) | 55° - 134 |         | 5509    | 5511    | 5513    | 5515    | 5517    | 5519    | 5521    |
| 11-12 | (290-320) | 60° - 154 |         | 609     | 611     | 613     | 615     | 617     | 619     | 621     |
| 12-14 | (320-370) | 70° - 174 |         |         | 711     | 713     | 715     | 717     | 719     | 721     |
| 14-14 | (370-450) | 80° - 194 |         |         |         |         |         |         |         | 821     |

### UGELLO BERIZZI

BRZ2

Esempio: Per un ugello con foro .012mm e angolo 30° ordinare BRZ312

Misure disponibili nella tabella sotto. Su richiesta ulteriori misure

| IN    | MM        | Angle     | .008-03 | .010-04 | .012-06 | .014-09 | .016-12 | .018-14 | .020-18 | .022-20 |
|-------|-----------|-----------|---------|---------|---------|---------|---------|---------|---------|---------|
| 2-3   | (50-90)   | 20° - 032 | 208     | 210     | 212     | 214     |         | 218     |         |         |
| 3-5   | (90-130)  | 25° - 052 | 2508    | 2510    | 2512    | 2514    |         |         | 2520    |         |
| 5-7   | (130-170) | 30° - 072 | 308     | 310     | 312     | 314     | 316     | 318     | 320     | 322     |
| 7-8   | (170-220) | 40° - 092 |         | 410     | 412     | 414     | 416     | 418     | 420     | 422     |
| 8-10  | (220-270) | 50° - 112 |         | 510     | 512     | 514     | 516     | 518     | 520     | 522     |
| 10-11 | (270-290) | 55° - 132 |         | 5510    | 5512    | 5514    | 5516    | 5518    | 5520    | 5522    |
| 11-12 | (290-320) | 60° - 152 |         | 610     | 612     | 614     | 616     | 618     | 620     | 622     |
| 12-14 | (320-370) | 70° - 172 |         |         |         |         | 716     | 718     | 720     | 722     |
| 14-14 | (370-450) | 80° - 192 |         |         |         |         |         |         |         | 822     |

## MISTO ARIA - MISURE UGELLI DISPONIBILI



### UGELLO TIPO GRACO

GWNXXX

Esempio: Per un ugello con foro .011mm e angolo 30° ordinare GWN311  
Misure disponibili nella tabella sotto. Su richiesta ulteriori misure

| IN    | MM        | Angolo | .007 | .009 | .011 | .013 | .015 | .017 | .019 | .021 |
|-------|-----------|--------|------|------|------|------|------|------|------|------|
| 2-4   | (50-102)  | 10°    | 107  | 109  | 111  |      |      |      |      |      |
| 4-6   | (102-152) | 20°    | 207  | 209  | 211  | 213  | 215  | 217  | 219  | 221  |
| 6-8   | (152-203) | 30°    | 307  | 309  | 311  | 313  | 315  | 317  | 319  | 321  |
| 8-10  | (203-254) | 40°    |      | 409  | 411  | 413  | 415  | 417  | 419  | 421  |
| 10-12 | (254-305) | 50°    |      | 509  | 511  | 513  | 515  | 517  | 519  | 521  |
| 12-14 | (305-356) | 60°    |      | 609  | 611  | 613  | 615  | 617  | 619  | 621  |
| 14-16 | (356-406) | 70°    |      |      | 711  | 713  | 715  | 717  | 719  | 721  |
| 16-18 | (406-457) | 80°    |      |      |      |      | 815  | 817  | 819  | 821  |
| 18-20 | (457-508) | 90°    |      |      |      |      |      | 917  | 919  | 921  |

### UGELLO TIPO GRACO

GWN2XXX

Esempio: Per un ugello con foro .010mm e angolo 30° ordinare GWN2310  
Misure disponibili nella tabella sotto. Su richiesta ulteriori misure

| IN    | MM        | Angolo | .008 | .010 | .012 | .014 | .016 |
|-------|-----------|--------|------|------|------|------|------|
| 4-6   | (102-152) | 20°    | 208  | 210  | 212  |      |      |
| 6-8   | (152-203) | 30°    | 308  | 310  | 312  |      |      |
| 8-10  | (203-254) | 40°    | 408  | 410  | 412  | 414  | 416  |
| 10-12 | (254-305) | 50°    |      | 510  | 512  | 514  | 516  |
| 12-14 | (305-356) | 60°    |      | 610  | 612  | 614  | 616  |
| 14-16 | (356-406) | 70°    |      | 710  | 712  | 714  | 716  |

## MISTO ARIA - MISURE UGELLI DISPONIBILI



### UGELLO MIX TIPO GRACO

GNNXXX

Esempio: Per un ugello con foro .011mm e angolo 30° ordinare GNN311

Misure disponibili nella tabella sotto. Su richiesta ulteriori misure

| IN    | MM        | Angolo | .007 | .009 | .011 | .013 | .015 | .017 | .019 | .021 |
|-------|-----------|--------|------|------|------|------|------|------|------|------|
| 2-4   | (50-102)  | 10°    | 107  | 109  | 111  |      |      |      |      |      |
| 4-6   | (102-152) | 20°    | 207  | 209  | 211  | 213  | 215  | 217  | 219  | 221  |
| 6-8   | (152-203) | 30°    | 307  | 309  | 311  | 313  | 315  | 317  | 319  | 321  |
| 8-10  | (203-254) | 40°    |      | 409  | 411  | 413  | 415  | 417  | 419  | 421  |
| 10-12 | (254-305) | 50°    |      | 509  | 511  | 513  | 515  | 517  | 519  | 521  |
| 12-14 | (305-356) | 60°    |      | 609  | 611  | 613  | 615  | 617  | 619  | 621  |
| 14-16 | (356-406) | 70°    |      |      | 711  | 713  | 715  | 717  | 719  | 721  |
| 16-18 | (406-457) | 80°    |      |      |      |      | 815  | 817  | 819  | 821  |
| 18-20 | (457-508) | 90°    |      |      |      |      |      | 917  | 919  | 921  |



### UGELLO MIX TIPO GRACO CON PREATOMIZZATORE

GN2XXX

Esempio: Per un ugello con foro .011mm e angolo 30° ordinare GN2311

Misure disponibili nella tabella sotto. Su richiesta ulteriori misure

| IN    | MM        | Angolo | .008 | .010 | .012 | .014 | .016 |
|-------|-----------|--------|------|------|------|------|------|
| 4-6   | (102-152) | 20°    | 208  | 210  | 212  |      |      |
| 6-8   | (152-203) | 30°    | 308  | 310  | 312  |      |      |
| 8-10  | (203-254) | 40°    | 408  | 410  | 412  | 414  | 416  |
| 10-12 | (254-305) | 50°    |      | 510  | 512  | 514  | 516  |
| 12-14 | (305-356) | 60°    |      | 610  | 612  | 614  | 616  |
| 14-16 | (356-406) | 70°    |      | 710  | 712  | 714  | 716  |

## MISTO ARIA - MISURE UGELLI DISPONIBILI



### UGELLO TIPO WAGNER

WGMXXX

Esempio: Per un ugello con foro .011mm e angolo 30° ordinare WGM311

Misure disponibili nella tabella sotto. Su richiesta ulteriori misure

| IN    | MM        | Angolo | .007 | .009 | .011 | .013 | .015 | .017 | .019 | .021 |
|-------|-----------|--------|------|------|------|------|------|------|------|------|
| 2-4   | (50-102)  | 10°    | 107  | 109  | 111  |      |      |      |      |      |
| 4-6   | (102-152) | 20°    | 207  | 209  | 211  | 213  | 215  | 217  | 219  | 221  |
| 6-8   | (152-203) | 30°    | 307  | 309  | 311  | 313  | 315  | 317  | 319  | 321  |
| 8-10  | (203-254) | 40°    |      | 409  | 411  | 413  | 415  | 417  | 419  | 421  |
| 10-12 | (254-305) | 50°    |      | 509  | 511  | 513  | 515  | 517  | 519  | 521  |
| 12-14 | (305-356) | 60°    |      | 609  | 611  | 613  | 615  | 617  | 619  | 621  |
| 14-16 | (356-406) | 70°    |      |      | 711  | 713  | 715  | 717  | 719  | 721  |
| 16-18 | (406-457) | 80°    |      |      |      |      | 815  | 817  | 819  | 821  |
| 18-20 | (457-508) | 90°    |      |      |      |      |      | 917  | 919  | 921  |



### UGELLO TIPO WAGNER

WGM2XXX

Esempio: Per un ugello con foro .010mm e angolo 30° ordinare WGM2310

Misure disponibili nella tabella sotto. Su richiesta ulteriori misure

| IN    | MM        | Angolo | .008 | .010 | .012 | .014 | .016 |
|-------|-----------|--------|------|------|------|------|------|
| 4-6   | (102-152) | 20°    | 208  | 210  | 212  |      |      |
| 6-8   | (152-203) | 30°    | 308  | 310  | 312  |      |      |
| 8-10  | (203-254) | 40°    | 408  | 410  | 412  | 414  | 416  |
| 10-12 | (254-305) | 50°    |      | 510  | 512  | 514  | 516  |
| 12-14 | (305-356) | 60°    |      | 610  | 612  | 614  | 616  |
| 14-16 | (356-406) | 70°    |      | 710  | 712  | 714  | 716  |

## MISTO ARIA - MISURE UGELLI DISPONIBILI



### UGELLO MIX TIPO OPTIMA

OPNXXX

Esempio: Per un ugello con foro .028mm e angolo 30° ordinare OPN328  
Misure disponibili nella tabella sotto. Su richiesta ulteriori misure

| IN    | MM        | Angolo | 0.18 0.007 | 0.23 .009 | 0.28 0.011 | 0.33 0.013 | 0.38 0.015 | 0.43 0.017 | .048 0.019 | .053 0.021 |
|-------|-----------|--------|------------|-----------|------------|------------|------------|------------|------------|------------|
| 4-6   | (102-152) | 20°    | 218        | 223       | 228        | 233        | 238        | 243        | 248        | 253        |
| 6-8   | (152-203) | 30°    | 318        | 323       | 328        | 333        | 338        | 343        | 348        | 353        |
| 8-10  | (203-254) | 40°    | 418        | 423       | 428        | 433        | 438        | 443        | 448        | 453        |
| 10-12 | (254-305) | 50°    | 518        | 523       | 528        | 533        | 538        | 543        | 548        | 553        |
| 12-14 | (305-356) | 60°    | 618        | 623       | 628        | 633        | 638        | 643        | 648        | 653        |



### UGELLO MIX TIPO OPTIMA

ONXXX

Esempio: Per un ugello con foro .028mm e angolo 30° ordinare ON328  
Misure disponibili nella tabella sotto. Su richiesta ulteriori misure

| IN    | MM        | Angolo | 0.18 0.007 | 0.23 .009 | 0.28 0.011 | 0.33 0.013 | 0.38 0.015 | 0.43 0.017 | .048 0.019 | .053 0.021 |
|-------|-----------|--------|------------|-----------|------------|------------|------------|------------|------------|------------|
| 4-6   | (102-152) | 20°    | 218        | 223       | 228        | 233        | 238        | 243        | 248        | 253        |
| 6-8   | (152-203) | 30°    | 318        | 323       | 328        | 333        | 338        | 343        | 348        | 353        |
| 8-10  | (203-254) | 40°    | 418        | 423       | 428        | 433        | 438        | 443        | 448        | 453        |
| 10-12 | (254-305) | 50°    | 518        | 523       | 528        | 533        | 538        | 543        | 548        | 553        |
| 12-14 | (305-356) | 60°    | 618        | 623       | 628        | 633        | 638        | 643        | 648        | 653        |

## AIRLESS - MISURE UGELLI DISPONIBILI



### UGELLO STANDARD

STXXX

Esempio: Per un ugello con foro .011mm e angolo 30°, ordinare ST311

Misure disponibili nella tabella sotto. Su richiesta ulteriori misure

| IN    | MM        | A°  | .007 | .009 | .011 | .013 | .015 | .017 | .019 | .021 | .023 | .025 | .027 | .029 | .031 | .033 | .035 | .037 | .039 | .041 | .043 | .045 | .047 | .049 | .051 | .053 | .055 | .063 | .065 |
|-------|-----------|-----|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|
| 2-4   | (50-102)  | 10° | 107  | 109  | 111  | 113  | 115  | 117  |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |
| 4-6   | (102-152) | 20° | 207  | 209  | 211  | 213  | 215  | 217  | 219  | 221  | 223  | 225  |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |
| 6-8   | (152-203) | 30° | 307  | 309  | 311  | 313  | 315  | 317  | 319  | 321  | 323  | 325  | 327  | 329  | 331  | 333  | 335  | 337  | 339  | 341  | 343  |      |      |      |      |      |      |      |      |
| 8-10  | (203-254) | 40° | 407  | 409  | 411  | 413  | 415  | 417  | 419  | 421  | 423  | 425  | 427  | 429  | 431  | 433  | 435  | 437  | 439  | 441  | 443  | 445  | 447  | 449  | 451  | 453  | 455  | 463  | 465  |
| 10-12 | (254-305) | 50° |      | 509  | 511  | 513  | 515  | 517  | 519  | 521  | 523  | 525  | 527  | 529  | 531  | 533  | 535  | 537  | 539  | 541  | 543  | 545  | 547  | 549  | 551  | 553  | 555  | 563  | 565  |
| 12-14 | (305-356) | 60° |      | 609  | 611  | 613  | 615  | 617  | 619  | 621  | 623  | 625  | 627  | 629  | 631  | 633  | 635  | 637  | 639  | 641  | 643  | 645  | 647  | 649  | 651  | 653  | 655  | 663  | 665  |
| 14-16 | (356-406) | 70° |      |      |      | 713  | 715  | 717  | 719  | 721  | 723  | 725  | 727  | 729  | 731  | 733  | 735  | 737  | 739  | 741  | 743  | 745  | 747  | 749  | 751  | 753  | 755  | 763  | 765  |
| 16-18 | (406-457) | 80° |      |      |      | 813  | 815  | 817  | 819  | 821  | 823  | 825  | 827  | 829  | 831  | 833  | 835  | 837  | 839  | 841  | 843  |      |      |      |      |      |      |      |      |
| 18-20 | (457-508) | 90° |      |      |      |      |      | 917  | 919  | 921  | 923  | 925  | 927  | 929  | 931  | 933  | 935  | 937  | 939  | 941  | 943  |      |      |      |      |      |      |      |      |



### UGELLO STANDARD FINE FINISH

STFXXX

Esempio: Per un ugello con foro .011 e angolo 30° ordinare STF311

Misure disponibili nella tabella sotto. Su richiesta ulteriori misure

| IN    | MM        | A°  | .007 | .009 | .011 | .013 | .015 | .017 | .019 | .021 | .023 | .025 | .027 | .029 | .031 | .033 | .035 | .037 | .039 | .041 | .043 | .045 | .047 | .049 | .051 | .053 | .055 | .063 | .065 |
|-------|-----------|-----|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|
| 2-4   | (50-102)  | 10° | 107  | 109  | 111  | 113  | 115  | 117  |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |
| 4-6   | (102-152) | 20° | 207  | 209  | 211  | 213  | 215  | 217  | 219  | 221  | 223  | 225  |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |
| 6-8   | (152-203) | 30° | 307  | 309  | 311  | 313  | 315  | 317  | 319  | 321  | 323  | 325  | 327  | 329  | 331  | 333  | 335  | 337  | 339  | 341  | 343  |      |      |      |      |      |      |      |      |
| 8-10  | (203-254) | 40° | 407  | 409  | 411  | 413  | 415  | 417  | 419  | 421  | 423  | 425  | 427  | 429  | 431  | 433  | 435  | 437  | 439  | 441  | 443  | 445  | 447  | 449  | 451  | 453  | 455  | 463  | 465  |
| 10-12 | (254-305) | 50° |      | 509  | 511  | 513  | 515  | 517  | 519  | 521  | 523  | 525  | 527  | 529  | 531  | 533  | 535  | 537  | 539  | 541  | 543  | 545  | 547  | 549  | 551  | 553  | 555  | 563  | 565  |
| 12-14 | (305-356) | 60° |      | 609  | 611  | 613  | 615  | 617  | 619  | 621  | 623  | 625  | 627  | 629  | 631  | 633  | 635  | 637  | 639  | 641  | 643  | 645  | 647  | 649  | 651  | 653  | 655  | 663  | 665  |
| 14-16 | (356-406) | 70° |      |      | 711  | 713  | 715  | 717  | 719  | 721  | 723  | 725  | 727  | 729  | 731  | 733  | 735  | 737  | 739  | 741  | 743  | 745  | 747  | 749  | 751  | 753  | 755  | 763  | 765  |
| 16-18 | (406-457) | 80° |      |      | 811  | 813  | 815  | 817  | 819  | 821  | 823  | 825  | 827  | 829  | 831  | 833  | 835  | 837  | 839  | 841  | 843  |      |      |      |      |      |      |      |      |
| 18-20 | (457-508) | 90° |      |      |      |      |      | 917  | 919  | 921  | 923  | 925  | 927  | 929  | 931  | 933  | 935  | 937  | 939  | 941  | 943  |      |      |      |      |      |      |      |      |

## AIRLESS - MISURE UGELLI DISPONIBILI



### UGELLO STANDARD FINE FINISH

FFXXX

Esempio: Per un ugello con foro .010 e angolo 30° ordinare FF310  
Misure disponibili nella tabella sotto. Su richiesta ulteriori misure

| IN    | MM        | Angle | .008 | .010 | .012 | .014 | .016 | .018 | .020 | .022 | .024 | .026 | .028 | .030 | .032 |
|-------|-----------|-------|------|------|------|------|------|------|------|------|------|------|------|------|------|
| 2-4   | (50-102)  | 10°   | 108  | 110  |      |      |      |      |      |      |      |      |      |      |      |
| 4-6   | (102-152) | 20°   | 208  | 210  | 212  | 214  | 216  | 218  |      |      | 224  |      |      |      | 232  |
| 6-8   | (152-203) | 30°   | 308  | 310  | 312  | 314  | 316  | 318  |      |      |      |      |      |      |      |
| 8-10  | (203-254) | 40°   | 408  | 410  | 412  | 414  | 416  | 418  | 420  |      |      |      | 428  | 430  | 432  |
| 10-12 | (254-305) | 50°   | 508  | 510  | 512  | 514  | 516  | 518  | 520  | 522  |      |      | 528  | 530  |      |
| 12-14 | (305-356) | 60°   | 608  | 610  | 612  | 614  | 616  | 618  | 620  | 622  | 624  | 626  | 628  |      |      |
| 14-16 | (356-406) | 70°   | 708  | 710  | 712  | 714  | 716  | 718  |      |      |      |      |      |      |      |
| 16-18 | (406-457) | 80°   | 808  | 810  | 812  | 814  | 816  | 818  | 820  | 822  | 824  | 826  | 828  |      | 832  |
| 18-20 | (457-508) | 90°   |      |      | 912  | 914  |      | 918  |      |      | 924  | 926  |      |      |      |



### UGELLO FINE FINISH GRACO

FIXXXX

Esempio: Per un ugello con foro .010mm e angolo 30° ordinare FIX310  
Misure disponibili nella tabella sotto. Su richiesta ulteriori misure

| IN    | MM        | Angolo | .008 | .010 | .012 | .014 | .016 | .018 | .020 | .022 | .024 | .026 | .028 | .030 | .032 |
|-------|-----------|--------|------|------|------|------|------|------|------|------|------|------|------|------|------|
| 2-4   | (50-102)  | 10°    | 108  |      |      |      |      |      |      |      |      |      |      |      |      |
| 4-6   | (102-152) | 20°    | 208  | 210  | 212  | 214  | 216  | 218  |      |      | 224  |      |      |      | 232  |
| 6-8   | (152-203) | 30°    |      | 310  | 312  | 314  | 316  | 318  |      |      |      |      |      |      |      |
| 8-10  | (203-254) | 40°    | 408  | 410  | 412  | 414  | 416  | 418  | 420  |      |      |      | 428  | 430  | 432  |
| 10-12 | (254-305) | 50°    |      | 510  | 512  | 514  | 516  | 518  | 520  | 522  |      |      | 528  | 530  |      |
| 12-14 | (305-356) | 60°    |      | 610  | 612  | 614  | 616  | 618  | 620  | 622  | 624  | 626  |      |      |      |
| 14-16 | (356-406) | 70°    |      |      | 712  | 714  | 716  | 718  |      |      |      |      |      |      |      |
| 16-18 | (406-457) | 80°    |      |      |      | 814  | 816  | 818  | 820  | 822  | 824  | 826  | 828  |      | 832  |
| 18-20 | (457-508) | 90°    |      |      | 912  |      |      | 918  |      |      | 924  |      |      |      |      |



## AIRLESS - MISURE UGELLI DISPONIBILI



### UGELLO REVERSIBILE PREATOMIZZATO

FM6XXX

Esempio: Per un ugello con foro .011mm e angolo 30° ordinare FM6311  
Misure disponibili nella tabella sotto. Su richiesta ulteriori misure

| IN    | MM        | A°  | .007 | .009 | .011 | .013 | .015 | .017 | .019 | .021 | .023 | .025 | .027 | .029 | .031 | .033 | .035 | .037 | .039 | .041 | .043 | .045 | .047 | .049 | .051 | .053 | .055 | .063 | .065 |
|-------|-----------|-----|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|
| 2-4   | (50-102)  | 10° |      | 109  | 111  | 113  | 115  | 117  |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |
| 4-6   | (102-152) | 20° | 207  | 209  | 211  | 213  | 215  | 217  | 219  | 221  | 223  | 225  |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |
| 6-8   | (152-203) | 30° | 307  | 309  | 311  | 313  | 315  | 317  | 319  | 321  | 323  | 325  | 327  | 329  | 331  | 333  | 335  | 337  | 339  | 341  | 343  |      |      |      |      |      |      |      |      |
| 8-10  | (203-254) | 40° | 407  | 409  | 411  | 413  | 415  | 417  | 419  | 421  | 423  | 425  | 427  | 429  | 431  | 433  | 435  | 437  | 439  | 441  | 443  | 445  | 447  | 449  | 451  | 453  | 455  |      | 465  |
| 10-12 | (254-305) | 50° |      | 509  | 511  | 513  | 515  | 517  | 519  | 521  | 523  | 525  | 527  | 529  | 531  | 533  | 535  |      | 539  | 541  | 543  | 545  | 547  | 549  | 551  | 553  | 555  | 563  | 565  |
| 12-14 | (305-356) | 60° |      | 609  | 611  | 613  | 615  | 617  | 619  | 621  | 623  | 625  | 627  | 629  | 631  | 633  | 635  |      | 639  | 641  | 643  | 645  | 647  | 649  | 651  | 653  | 655  | 663  | 665  |
| 14-16 | (356-406) | 70° |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |
| 16-18 | (406-457) | 80° |      |      |      | 813  | 815  | 817  | 819  | 821  | 823  | 825  | 827  | 829  | 831  | 833  | 835  |      | 839  | 841  | 843  |      |      |      |      |      |      |      |      |
| 18-20 | (457-508) | 90° |      |      |      |      |      | 917  | 919  | 921  | 923  | 925  | 927  | 929  | 931  | 933  | 935  |      | 939  | 941  | 943  |      |      |      |      |      |      |      |      |



### UGELLO REVERSIBILE PREATOMIZZATO

FMC6XXX

Esempio: Per un ugello con foro .010mm e angolo 30° ordinare FMC6310  
Misure disponibili nella tabella sotto. Su richiesta ulteriori misure

| IN    | MM          | Angolo | .008 | .010 | .012 | .014 | .016 | .018 |
|-------|-------------|--------|------|------|------|------|------|------|
| 2-4   | (5-10)      | 10°    | 108  | 110  | 112  | 114  |      |      |
| 4-6   | (10-15)     | 20°    | 208  | 210  | 212  | 214  |      |      |
| 6-8   | (15-20)     | 30°    | 308  | 310  | 312  | 314  |      |      |
| 8-10  | (20-25.5)   | 40°    | 408  | 410  | 412  | 414  |      |      |
| 10-12 | (25.5-30.5) | 50°    |      | 510  | 512  | 514  | 516  | 518  |
| 12-14 | (30.5-35.5) | 60°    |      |      | 612  | 614  | 616  | 618  |

## AIRLESS - MISURE UGELLI DISPONIBILI



### UGELLO REVERSIBILE PER TRACCIALINEE

FMLMXXX

Esempio: Per un ugello con foro .013mm e angolo 20° ordinare FMLM213  
Misure disponibili nella tabella sotto. Su richiesta ulteriori misure

| IN    | MM          | Angolo | .013 | .015 | .017 | .019 | .021 | .023 | .025 | .027 | .029 | .031 | .035 |
|-------|-------------|--------|------|------|------|------|------|------|------|------|------|------|------|
| 4-6   | (10-15)     | 20°    | 213  | 215  | 217  | 219  |      |      |      |      |      |      |      |
| 6-8   | (15-20)     | 30°    |      | 315  | 317  | 319  | 321  | 323  | 325  | 327  | 329  | 331  |      |
| 8-10  | (20-25.5)   | 40°    |      |      | 417  | 419  | 421  | 423  | 425  | 427  | 429  | 431  | 435  |
| 12-14 | (30.5-35.5) | 60°    |      |      |      |      | 621  | 623  | 625  | 627  | 629  | 631  | 635  |



### UGELLO REVERSIBILE RAC5

FM6XXX

Esempio: Per un ugello con foro .011 e angolo 30° ordinare RACV311  
Misure disponibili nella tabella sotto. Su richiesta ulteriori misure

| IN    | MM        | A°  | .007 | .009 | .011 | .013 | .015 | .017 | .019 | .021 | .023 | .025 | .027 | .029 | .031 | .033 | .035 | .037 | .039 | .041 | .043 | .045 | .047 | .049 |
|-------|-----------|-----|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|
| 2-4   | (50-102)  | 10° |      | 109  | 111  | 113  | 115  |      | 119  |      |      |      |      |      |      |      |      |      |      |      |      |      |      |      |
| 4-6   | (102-152) | 20° | 207  | 209  | 211  | 213  | 215  | 217  | 219  | 221  | 223  | 225  |      |      |      | 235  |      |      |      |      |      |      |      |      |
| 6-8   | (152-203) | 30° | 307  | 309  | 311  | 313  | 315  | 317  | 319  | 321  | 323  | 325  | 327  |      | 331  |      |      |      |      |      |      |      |      |      |
| 8-10  | (203-254) | 40° |      | 409  | 411  | 413  | 415  | 417  | 419  | 421  | 423  | 425  | 427  | 429  | 431  | 433  | 435  | 439  | 443  |      | 451  | 455  |      |      |
| 10-12 | (254-305) | 50° |      | 509  | 511  | 513  | 515  | 517  | 519  | 521  | 523  | 525  | 527  | 529  | 531  | 533  | 535  |      | 543  |      | 551  | 555  | 563  |      |
| 12-14 | (305-356) | 60° |      | 609  | 611  | 613  | 615  | 617  | 619  | 621  | 623  | 625  | 627  | 629  | 631  | 633  | 635  |      |      | 645  |      | 655  |      | 665  |
| 14-16 | (356-406) | 70° |      |      |      |      |      |      |      | 721  | 723  | 725  |      | 729  |      |      | 735  |      |      |      |      |      |      |      |
| 16-18 | (406-457) | 80° |      |      |      |      | 815  | 817  | 819  | 821  |      |      | 827  |      | 831  | 833  | 835  |      |      |      |      |      |      |      |
| 18-20 | (457-508) | 90° |      |      |      |      |      | 917  |      |      |      |      |      |      |      |      | 935  |      |      |      |      |      |      |      |