

# APOLLO 30

Pneumatic air-assisted airless piston pump

CE  II 2GT6 X

Pneumatic air-assisted airless piston pump for medium pressure professional paint spraying suitable for the wood and metal sectors with medium-high viscosity enamels, lacquers, base coats and varnishes, water-based or solvent. Available in the airless model.



CODE	DESCRIPTION
TKB30G	APOLLO 30 Piston pneumatic air-assisted airless pump C/ Trolley - Pressure regulation control plate - Stainless steel inline filter - Twin hose HP 7,5 m - Mach3 spray gun - Complete suction system
TKB30H	APOLLO 30 Piston pneumatic air-assisted airless pump C/ Trolley - Pressure regulation control plate - Stainless steel inline filter - Twin hose HP 7,5 m - Mach3 spray gun - Gravity tank with adapter
TKB30E	APOLLO 30 Piston pneumatic air-assisted airless pump C/ Trolley - Pressure regulation control plate - Stainless steel inline filter - Complete suction system
TKB30F	APOLLO 30 Piston pneumatic air-assisted airless pump on bracket - Pressure regulator - Stainless steel inline filter

---

**TKB30I**      **APOLLO 30 Piston pneumatic air-assisted airless pump on bracket - Pressure regulator - Stainless steel inline filter**

---

---

**TKB30C**      **APOLLO 30 Piston pneumatic pump C/ Stainless steel inline filter**

---

## Technical specifications

Ratio: 30:1

Pump capacity per cycle: cm<sup>3</sup> 37

Stroke: mm 100

Max. Delivery free flow: ltr/min 7,0

Number of stroke per liter: 27

Max. Working outlet pressure: Bar (PSI) 240 (3480)

Max. Air inlet pressure: Bar (PSI) 8 (116)

Weight: kg. 27

Air consumption: ltr/min 250 - 750

Packing type: Fix

Material inlet fitting size: M 3/4"

Material outlet fitting size: M 1/4"

Packing material: PTFE - PE