

# APOLLO 30

Piston pneumatic airless pump

CE  II 2GT6 X

Piston pneumatic airless pump for medium pressure professional paint spraying suitable for the wood and metal sectors with medium-high viscosity enamels, lacquers, base coats and varnishes, water-based or solvent. Available in the air-assisted airless model.



CODE	DESCRIPTION
TKB30L	APOLLO 30 Piston pneumatic airless pump C/ Trolley - Pressure regulation control plate - Stainless steel inline filter - HP hose 7,5 m - RST1 spray gun - FM6 tip guard - Reversible FM6 tip - Complete suction system
TKB30M	APOLLO 30 Piston pneumatic airless pump C/ Trolley - Pressure regulation control plate - Stainless steel inline filter - HP hose 7,5 m - RST1 spray gun - FM6 tip guard - Reversible FM6 tip - Gravity tank with adapter
TKB30A	APOLLO 30 Piston pneumatic airless pump C/ Trolley - Pressure regulation control plate - Stainless steel inline filter - Complete suction system
TKB30D	APOLLO 30 Piston pneumatic airless pump C/ Trolley - Pressure regulation control plate - Stainless

steel inline filter - Gravity tank with adapter

---

---

**TKB30B**      **APOLLO 30 Piston pneumatic airless pump on bracket - Pressure regulation control plate - Stainless steel inline filter**

---

---

**TKB30C**      **APOLLO 30 Piston pneumatic pump C/ Stainless steel inline filter**

---

## Technical specifications

Ratio: 30:1

Pump capacity per cycle: cm<sup>3</sup> 37

Stroke: mm 100

Max. Delivery free flow: ltr/min 7,0

Number of stroke per liter: 27

Max. Working outlet pressure: Bar (PSI) 240 (3480)

Max. Air inlet pressure: Bar (PSI) 8 (116)

Weight: kg. 27

Air consumption: ltr/min 250 - 750

Packing type: Fix

Material inlet fitting size: M 3/4"

Material outlet fitting size: M 1/4"

Packing material: PTFE - PE