

APOLLO 303R

Inverted piston pneumatic pump

CE  II 2GT6 X

Inverted piston pneumatic air-assisted airless pump for medium pressure professional paint spraying, airless or airless-assisted, suitable for the wood and metal sectors with low and medium viscosity enamels, lacquers, base coats and varnishes.



CODE	DESCRIPTION
TKP303H	APOLLO 303R Air-assisted airless inverted pump C/ Trolley - Pressure regulation control plate - Stainless steel inline filter - Twin hose 7,5m - Mach3 spray gun - Gravity tank
TKP303D	APOLLO 303R Air-assisted airless inverted pump C/ Trolley - Pressure regulation control plate - Stainless steel inline filter - Twin hose 7,5m - Mach3 spray gun - Gravity tank
TKP303I	APOLLO 303R Air-assisted airless inverted pump on bracket - Pressure regulator - Stainless steel inline filter - Gravity tank

Technical specifications

Ratio: 30:1

Pump capacity per cycle: cm³ 40

Stroke. mm 60

Max. Delivery free flow: ltr/min 4,0

Number of stroke per liter: 25

Max. Working outlet pressure: Bar (PSI) 240 (3480)

Max. Air inlet pressure: Bar (PSI) 8 (116)

Weight: kg. 14

Air consumption: ltr/min 250 - 400

Packing type: Fix

Material inlet fitting size: M 3/4"

Material outlet fitting size: M 1/4"

Packing material: PTFE - PE