

APOLLO 303

Pneumatic Piston Pump

CE  II 2GT6 X

Piston pneumatic air-assisted airless pump for medium pressure professional paint spraying assisted-airless, suitable for the wood and metal sectors with low and medium viscosity enamels, lacquers, base coats and varnishes.



CODE	DESCRIPTION
TKP303B	APOLLO 303 Pneumatic air-assisted airless pump C/ Trolley - Pressure regulation control plate - Stainless steel inline filter - Twin hose HP 7,5 m - Mach3 spray gun - Suction system
TKP303F	APOLLO 303 Pneumatic air-assisted airless pump C/ Trolley - Pressure regulation control plate - Stainless steel inline filter - Twin hose HP 7,5 m - Mach3 spray gun - Gravity tank with adapter
TKP303E	APOLLO 303 Pneumatic air-assisted airless pump C/ Trolley - Pressure regulation control plate - Stainless steel inline filter - Suction system
TKP303A	APOLLO 303 Pneumatic air-assisted airless pump C/ Trolley - Pressure regulation control plate - Stainless steel inline filter - Gravity tank with adapter

TKP303C	APOLLO 303 Pneumatic air-assisted airless pump on bracket - Pressure regulator - Stainless steel inline filter
----------------	---

TKP303G	APOLLO 303 Pneumatic air-assisted airless pump C/ Stainless steel inline filter
----------------	--

Technical specifications

Ratio: 30:1

Pump capacity per cycle: cm³ 40

Stroke. mm 60

Max. Delivery free flow ltr/min: 4,0

Number of stroke per liter: 25

Max. Working outlet pressure: Bar (PSI) 240 (3480)

Max. Air inlet pressure: Bar (PSI) 8 (116)

Weight: kg. 14

Air consumption: ltr/min 250 - 400

Packing type: Fix

Material inlet fitting size: M 3/4"

Material outlet fitting size: M 1/4"

Packing material: PTFE - PE