


APOLLO 30 Transfer

Piston Pneumatic Transfer Pump

CE  II 2GT6 X

Fluid transfer pneumatic piston pump suitable for rapid fluid handling in the naval, industrial and refinery sectors with paint, waste fluids, motor oil, gear oil, hydraulic fluid, oil and grease in general. Available in two different ratios and capacities (3:1 and 6:1).



CODE	DESCRIPTION
TKP5031A	APOLLO 30 Transfer 3:1 Piston pneumatic transfer pump on bracket - Pressure regulator - Complete suction system
TKP5031B	APOLLO 30 Transfer 3:1 Bare piston pneumatic transfer pump
TKP2561A	APOLLO 30 Transfer 6:1 Piston pneumatic transfer pump on bracket - Pressure regulator - Complete suction system
TKP2561B	APOLLO 30 Transfer 6:1 Bare piston pneumatic transfer pump

Technical specifications

APOLLO 30 TRANSFER 3:1

Ratio: 3:1

Pump capacity per cycle: cm³ 667

Stroke: mm 100

Max. Delivery free flow: ltr/min 42

Number of stroke per liter: 1.5

Max. Working outlet pressure: Bar (PSI) 24 (348)

Max. Air inlet pressure: Bar (PSI) 8 (116)

Weight: kg.18

Air consumption: ltr/min 600 - 2650

Packing type: Mobile

Material inlet fitting size: M 36x2 mm

Material outlet fitting size: M 3/4"

Packing material: PTFE - PE

APOLLO 30 TRANSFER 6:1

Ratio: 6:1

Pump capacity per cycle: cm³ 334

Stroke: mm 100

Max. Delivery free flow: ltr/min 30

Number of stroke per liter: 3

Max. Working outlet pressure: Bar (PSI) 48 (696)

Max. Air inlet pressure: Bar (PSI) 8 (116)

Weight: kg. 15

Air consumption: ltr/min 600 - 2650

Packing type: Mobile

Material inlet fitting size: M 36x2 mm

Material outlet fitting size: M 3/4"

Packing material: PTFE - PE