


APOLLO 40

Pneumatic airless piston pump

CE  II 2GT6 X

Pneumatic airless piston pump for medium pressure professional paint spraying suitable for the wood and metal sectors with medium-high viscosity enamels, lacquers, base coats and varnishes, water-based or solvent. Available in the airless model.



CODE	DESCRIPTION
TKP401AB	APOLLO 40 Piston pneumatic air-assisted airless pump C/ Trolley - Pressure regulation control plate - Stainless steel inline filter - Twin hose HP 7,5m - Mach3 spray gun - Complete suction system
TKP401AC	APOLLO 40 Piston pneumatic air-assisted airless pump C/ Trolley - Pressure regulation control plate - Stainless steel inline filter - Twin hose HP 7,5m - Mach3 spray gun - Gravity tank with adapter
TKP401AA	APOLLO 40 Piston pneumatic air-assisted airless pump C/ Trolley - Pressure regulation control plate - Stainless steel inline filter - Complete suction system
TKP401AD	APOLLO 40 Piston pneumatic air-assisted airless pump C/ Trolley - Pressure regulation control

plate - Stainless steel inline filter - Gravity tank with adapter

TKP401AE APOLLO 40 Piston pneumatic air-assisted airless pump on bracket - Pressure regulators - Stainless steel inline filter

TKP401F APOLLO 40 Piston pneumatic air-assisted airless pump C/ Stainless steel inline filter

Technical specifications

Ratio: 40:1

Pump capacity per cycle: cm³ 50

Stroke: mm 80

Max. Delivery free flow: ltr/min 9

Number of stroke per liter: 20

Max. Working outlet pressure: Bar (PSI) 320 (4640)

Max. Air inlet pressure: Bar (PSI) 8 (116)

Weight: kg. 32

Air consumption: ltr/min 250 - 1000

Packing type: Mobile

Material inlet fitting size: M 36x2 mm

Material outlet fitting size: M 1/4"

Packing material: PTFE-PE-LEATHER