

APOLLO 40

Piston pneumatic airless pump

CE  II 2GT6 X

Piston pneumatic airless pump for medium pressure professional paint spraying suitable for the wood and metal sectors with medium-high viscosity enamels, lacquers, base coats and varnishes, water-based or solvent. Available in the air-assisted airless model.



CODE	DESCRIPTION
TKP401B	APOLLO 40 Piston pneumatic airless pump C/ Trolley - Pressure regulation control plate - Stainless steel inline filter - HP hose 7,5m - RST2 spray gun - FM6 tip guard - Reversible FM6 tip - Complete suction system
TKP401D	APOLLO 40 Piston pneumatic airless pump C/ Trolley - Pressure regulation control plate - Stainless steel inline filter - HP hose 7,5m - RST2 spray gun - FM6 tip guard - Reversible FM6 tip - Gravity tank with adapter
TKP401A	APOLLO 40 Piston pneumatic airless pump C/ Trolley - Pressure regulation control plate - Stainless steel inline filter - Complete suction system
TKP401E	APOLLO 40 Piston pneumatic airless pump C/ Trolley - Pressure regulation control plate - Stainless

steel inline filter - Gravity tank with adapter

TKP401C	APOLLO 40 Piston pneumatic airless pump on bracket with pressure regulators - Stainless steel inline filter
---------	---

TKP401F	APOLLO 40 Piston pneumatic airless pump C/ Stainless steel inline filter
---------	--

Technical specifications

Ratio: 40:1

Pump capacity per cycle: cm³ 50

Stroke: mm 80

Max. Delivery free flow: ltr/min 9

Number of stroke per liter: 20

Max. Working outlet pressure: Bar (PSI) 320 (4640)

Max. Air inlet pressure: Bar (PSI) 8 (116)

Weight: kg. 32

Air consumption: ltr/min 250 - 1000

Packing type: Mobile

Material inlet fitting size: M 36x2 mm

Material outlet fitting size: M 1/4"

Packing material: PTFE-PE-LEATHER