

APOLLO 48

Pneumatic piston pump

CE  II 2GT6 X

Pneumatic airless piston pump for high pressure professional paint spraying, suitable for treating paint and anti-corrosion with high viscosity products. It can be used in the naval, civil and industrial construction sectors and heavy carpentry, with paint, anti-corrosives, intumescent coatings, protective coatings and encapsulants (water-based and solvent), putties, ready-mix stucco, fillers and mural injection resins.



CODE	DESCRIPTION
TKP4825C	APOLLO 48 Pneumatic airless piston pump C/ Trolley - Pressure regulator - Stainless steel inline filter - HP hose 10m - RST2 spray gun - FM6 tip guard - Reversible FM6 tip - Complete suction system
TKP4825A	APOLLO 48 Pneumatic airless piston pump C/ Trolley - Pressure regulator - Stainless steel inline filter - Complete suction system
TKP4825B	APOLLO 48 Pneumatic airless piston pump on bracket - Pressure regulator - Stainless steel inline filter

TKP4825D

APOLLO 48 Pneumatic airless piston pump C/ Stainless steel inline filter

Technical specifications

Ratio: 48:1

Pump capacity per cycle: cm³ 143

Stroke: mm 100

Max. Delivery free flow : ltr/min 18

Number of stroke per liter: 7

Max. Working outlet pressure: Bar (PSI) 384 (5569)

Max. Air inlet pressure: Bar (PSI) 8 (116)

Weight: kg. 64

Air consumption: ltr/min 600 - 2650

Packing type: Fix

Material inlet fitting size: M 36X2 mm

Material outlet fitting size: M 16x1,5 mm

Packing material: PTFE-PE-LEATHER