


APOLLO 66

Pneumatic Airless Piston Pump



Pneumatic airless piston pump for high pressure professional paint spraying, suitable for treating paint and anti-corrosion with high viscosity products.



CODE	DESCRIPTION
TKP6618C	APOLLO 66 Pneumatic airless piston pump C/ Trolley - Pressure regulator - Stainless steel inline filter - HP hose 10m - RST2 spray gun - FM6 tip guard - Reversible FM6 tip - Complete suction system
TKP6618A	APOLLO 66 Pneumatic airless piston pump C/ Trolley - Pressure regulator - Stainless steel inline filter - Complete suction system
TKP6618B	APOLLO 66 Pneumatic airless piston pump on bracket - Pressure regulator - Stainless steel inline filter
TKP6618D	APOLLO 66 Pneumatic airless piston pump C/ Stainless steel inline filter

Technical specifications

Ratio: 66:1

Pump Capacity per cycle: cm³ 100

Stroke: mm 100

Max Delivery Free Flow: ltr/min 15

Number of stroke per liter: 10

Max. Working outlet Pressure: Bar (psi) 528 (4640)

Max. Air Inlet Pressure: Bar (psi) 8 (116)

Weight: kg. 64

Air Consumption: ltr/min 600-2650

Packing type: Fix

Material inlet fitting size: M 36x2 mm

Material outlet fitting size: M 16x1,5 mm

Packing material: PTFE-PE-LEATHER