

B24 mix

Pneumatic Double Diaphragm pump

Two component double diaphragm pneumatic pump suitable for low-pressure air spraying with paint atomization air. It can be used with bicomponent products, enamels, lacquers, low and medium viscosity base coats and varnishes, in the wood and metal sector.



CODE	DESCRIPTION
TK212401	B24 MIX Two component pneumatic double diaphragm pump C/ Trolley - Pressure regulator control plate - 2 Inline filters - Static mixer - LP hose 7,5m - Spray gun - 2 Complete suction systems BOXER Pneumatic double diaphragm flushing pump C/ Pressure regulator - Complete suction system
TK212400	B24 MIX Two component pneumatic double diaphragm pump C/ Trolley - Pressure regulator control plate - 2 Inline filters - Static mixer - 2 Complete suction systems BOXER Pneumatic double diaphragm flushing pump C/ Pressure regulator - Complete suction system

Technical specifications

Motor: Pneumatic

Ratio: 1:1

Max. Delivery free flow: ltr/min 12

Max. Air inlet pressure: Bar (PSI) 8 (116)

Max. Working outlet pressure: Bar (PSI) 8 (116)

Weight: kg. 45

Air consumption: ltr/min 250 - 400

Material inlet fitting size: M 1/2"

Material outlet fitting size: M 3/8"