


B24

Pneumatic Double Diaphragm pump

CE  II 2GT6 X

Double diaphragm pneumatic pump suitable for low-pressure air spraying with paint atomization air or low-medium viscosity fluid transfer. It can be used with enamels, lacquers, base coats and varnishes, in the wood and metal sector. Available in the plastic variant BOXER.



CODE	DESCRIPTION
212404	B24 Pneumatic double diaphragm pump C/ Trolley - Pressure regulator - Inline filter - Fluid regulator - LP hose 7,5m - Spray gun - Complete suction system
212405	B24 Pneumatic double diaphragm pump C/ Trolley - Pressure regulator - Inline filter - Fluid regulator - LP hose 7,5m - Spray gun - Gravity tank with adapter
212403	B24 Pneumatic double diaphragm pump C/ Trolley - Pressure regulator - Inline filter - Fluid regulator
212402	B24 Pneumatic double diaphragm pump C/ Trolley - Pressure regulator - Inline filter

212400 **B24 Pneumatic double diaphragm transfer pump C/ Pressure regulator**

212401 **B24 Bare pneumatic double diaphragm transfer pump**

TK13000 **BOXER Pneumatic double diaphragm transfer pump C/ Pressure regulator**

TK13001 **BOXER Bare pneumatic double diaphragm transfer pump**

Technical specifications

Motor: Pneumatic

Ratio: 1:1

Max. Delivery free flow: ltr/min 24

Max. Air inlet pressure: Bar (PSI) 8 (116)

Max. Working outlet pressure: Bar (PSI) 8 (116)

Weight: kg. 11

Air consumption: ltr/min 200 - 500

Material inlet fitting size: M 1/2"

Material outlet fitting size: M 3/8"