

MIURA 44000

Hydraulic Piston pump

Hydraulic piston pump for airless high-pressure professional paint spraying suitable for painting and anti-corrosion treatment with high viscosity products. It can be used with paints, anti-corrosives, intumescent coatings, protective coatings and encapsulants (water-based and solvent), putties, ready-mix stucco, fillers and mural injection resins. Available either with gas or electric engine.



CODE	DESCRIPTION
TKH44D	MIURA 44000 Hydraulic airless piston pump Volt 230/Hz50 single phase C/Trolley - Inline filter - Manometer - HP hose 10m - RST2 spray gun - FM6 tip guard - Reversible FM6 tip - Complete suction system
TKH44E	MIURA 44000 Hydraulic airless piston pump volt 230/ Hz50 single phase C/Trolley - Inline filter - Manometer - HP hose 10m - RST2 spray gun - FM6 tip guard - Reversible FM6 tip - Direct suction
TKH44C	MIURA 44000 Hydraulic airless piston pump volt 230/ Hz50 single phase C/Trolley - Inline filter - Manometer - Direct suction
TKH44A	MIURA 44000 Hydraulic airless piston pump volt 380/ Hz50 single phase C/Trolley - Inline filter - Manometer - Direct suction

TKH44B **MIURA 44000 Hydraulic airless piston pump with gas engine C/ Trolley - Inline filter - Manometer - Direct suction**

Technical specifications

Motor | Volt: **380 V**

Power: **4,0 Kw**

Max. Delivery Free Flow: ltr/min **14,2**

Stroke: mm **100**

1 Gun 0,063

Max. Tip **2 Guns 0,036**

3 Guns 0,023

Max. Working outlet pressure Bar (PSI) **280 (4061)**

Max length HP hose: mt. **150**

Max length HP hose (elevation): mt. **150**

Packing material: **PTFE**

Material outlet fitting size: **M 16x1,5 mm**

Motor: **HONDA**

Power: **11,7 HP**

Max. Delivery Free Flow: ltr/min **14,2**

Stroke: mm **100**

1 Gun 0,063

Max. Tip **2 Guns 0,036**

3 Guns 0,023

Max. Working outlet pressure: Bar (PSI) **280 (4061)**

Max length HP hose: mt. **150**

Max length HP hose (elevation): mt. **150**

Packing material: **PTFE**

Material outlet fitting size: **M 16x1,5 mm**

C

Motor: 230 V

Power : 2,23 Kw

Max. Delivery Free Flow: 10,5

Stroke: 100

1 Gun 0,037

Max. Tip 2 Gun 0,017

3 Gun ---

Max. Working outlet pressure: 240 (3480)

Max length HP hose: 150

Max length HP hose (elevation): 150

Packing material: PTFE

Material outlet fitting size: M 16x1,5 mm