

# TSUNAMI 11

Electric Diaphragm pump

Electric diaphragm pump for professional high-pressure airless paint spraying, suitable for the light construction sector for medium-large surfaces with medium-low viscosity mural products, enamels, lacquers, base coats and varnishes, medium and low viscosity water-based paints and mural injection resins.



CODE	DESCRIPTION
TKU11E	TSUNAMI 11 Electric airless diaphragm pump volt 230/Hz50 single phase and orizontal C/ Trolley - Manometer - HP hose 7,5m - RST2 spray gun - FM6 tip guard - Reversible FM6 tip - Complete suction system
TKU11F	TSUNAMI 11 Electric airless diaphragm pump volt 230/ Hz50 single phase and orizontal C/ Trolley - Manometer - HP hose 7,5m - RST2 spray gun - FM6 tip guard - Reversible FM6 tip - 35L Gravity tank
TKU11A	TSUNAMI 11 Electric airless diaphragm pump volt 230/ Hz50 single phase and orizontal C/ Trolley - Manometer - Complete suction system
TKU11D	TSUNAMI 11 Electric airless diaphragm pump volt 230/ Hz50 single phase and orizontal C/ Trolley - Manometer - 35L Gravity tank

## Technical specifications

Motor | Volt: 230 Volt/ 50 Hz

Variant: 380 Volt/ 110 Volt

Power: 2,23Kw

Max. Delivery Free Flow: ltr/min 9,5

1 Gun 0,043

Max. Tip 2 Guns 0,019

3 Guns --

Max. Working outlet pressure: Bar (PSI) 220 (3190)

Max length HP hose: mt. 100

Max length HP hose (elevation): mt. 100

Weight: kg. 54

Material inlet fitting size: M 36x2 mm

Material outlet fitting size: M 16x1,5 mm