

Tsunami 65

Electric Diaphragm pump

Electric diaphragm pump for professional high-pressure airless paint spraying, suitable for the light construction sector for medium-large surfaces with medium-low viscosity mural products, enamels, lacquers, base coats and varnishes, medium and low viscosity water-based paints and mural injection resins.



CODE	DESCRIPTION
TKU65E	TSUNAMI 65 Electric airless diaphragm pump volt 230/Hz50 single phase and orizontal C/ Trolley - Manometer - HP hose 7,5m - RST2 spray gun - FM6 tip guard - Reversible FM6 tip - Complete suction system
TKU65F	TSUNAMI 65 Electric airless diaphragm pump volt 230/ Hz50 single phase and orizontal C/ Trolley - Manometer - HP hose 7,5m - RST2 spray gun - FM6 tip guard - Reversible FM6 tip - 35L gravity tank
TKU65A	TSUNAMI 65 Electric airless diaphragm pump volt 230/ Hz50 single phase and orizontal C/ Trolley - Manometer - Complete suction system
TKU65D	TSUNAMI 65 Electric airless diaphragm pump volt 230/ Hz50 single phase and orizontal C/ Trolley - Manometer - 35L gravity tank

Technical specifications

Motor | Volt: 230 Volt/ 50 Hz

Variant: 380 Volt / 110 Volt

Power: 1,49 Kw

Max. Delivery Free Flow: ltr/min 7,5

1 Gun 0,037

Max. Tip 2 Guns 0,017

3 Guns —

Max. Working outlet pressure: Bar (PSI) 220 (3190)

Max length HP hose: mt. 100

Max length HP hose (elevation): mt. 100

Weight: kg. 54

Material inlet fitting size: M 36x2 mm

Material outlet fitting size: M 16x1,5 mm