

R7 TEXTILE HOSES WITH STEEL FITTINGS

R7 textile hoses with steel fittings



CODE	DESCRIPTION	Ø I mm	Ø E mm	WORKING PRESSURE max. bar	RADIUS min. mm	WEIGHT g/m	REEL mt	FERRULE CODE
KT7532	R7 textile hose 5/32"	6,4	13,5	267	25	41	200	BB1096
KT7316	R7 textile hose 3/16"	4,8	10	280	35	68	200	BB1090
KT7014	R7 textile hose 1/4"	6,4	11,8	270	50	87	200	BB1091
KT7038	R7 textile hose 3/8"	9,7	16	260	75	146	150	BB1092
KT7012	R7 textile hose 1/2"	13	20,3	140	95	214	100	BB1093

COD	DESCRIPTION	MT.	RACC.
716054T	Textile hose R7 3/16"	mt 5	conn. 1/4"
716754T	Textile hose R7 3/16"	mt 7,5	conn. 1/4"

716104T	Textile hose R7 3/16"	mt 10	conn. 1/4"
716154T	Textile hose R7 3/16"	mt 15	conn. 1/4"
716204T	Textile hose R7 3/16"	mt 20	conn. 1/4"
716055T	Textile hose R7 3/16"	mt 5	conn. 16x1,5
716755T	Textile hose R7 3/16"	mt 7,5	conn. 16x1,5
716105T	Textile hose R7 3/16"	mt 10	conn. 16x1,5
716155T	Textile hose R7 3/16"	mt 15	conn. 16x1,5
716205T	Textile hose R7 3/16"	mt 20	conn. 16x1,5

Conn. Steel-Hose 3/16" -Press. max: 280 Bar (Psi 4060)

COD	DESCRIPTION	MT.	RACC.
714054T	Textile hose R7 1/4"	mt 5	conn. 1/4"
714754T	Textile hose R7 1/4"	mt 7,5	conn. 1/4"
714104T	Textile hose R7 1/4"	mt 10	conn. 1/4"
714154T	Textile hose R7 1/4"	mt 15	conn. 1/4"
714204T	Textile hose R7 1/4"	mt 20	conn. 1/4"
714055T	Textile hose R7 1/4"	mt 5	conn. 16x1,5
714755T	Textile hose R7 1/4"	mt 7,5	conn. 16x1,5
714105T	Textile hose R7 1/4"	mt 10	conn. 16x1,5

714155T	Textile hose R7 1/4"	mt 15	conn. 16x1,5
714205T	Textile hose R7 1/4"	mt 20	conn. 16x1,5
714058T	Textile hose R7 1/4"	mt 5	conn. 3/8"
714758T	Textile hose R7 1/4"	mt 7,5	conn. 3/8"
714108T	Textile hose R7 1/4"	mt 10	conn. 3/8"
714158T	Textile hose R7 1/4"	mt 15	conn. 3/8"
714208T	Textile hose R7 1/4"	mt 20	conn. 3/8"

Conn. Steel - Hose 1/4" -Press. max: 270 Bar (Psi 3915)

COD	DESCRIPTION	MT.	RACC.
738055T	Textile hose R7 3/8"	mt 5	racc 16x1,5
738755T	Textile hose R7 3/8"	mt 7,5	racc 16x1,5
738105T	Textile hose R7 3/8"	mt 10	racc 16x1,5
738155T	Textile hose R7 3/8"	mt 15	racc 16x1,5
738205T	Textile hose R7 3/8"	mt 20	racc 16x1,5
738058T	Textile hose R7 3/8"	mt 5	racc 3/8"
738758T	Textile hose R7 3/8"	mt 7,5	racc 3/8"
738108T	Textile hose R7 3/8"	mt 10	racc 3/8"

738158T	Textile hose R7 3/8"	mt 15	racc 3/8"
738208T	Textile hose R7 3/8"	mt 20	racc 3/8"
Conn. Steel -Hose 3/8" - Press. max: 260 Bar (Psi 3770)			
COD	DESCRIPTION	MT.	RACC.
715054T	Textile hose R7 5/32"	mt 5	racc 1/4"
715754T	Textile hose R7 5/32"	mt 7,5	racc 1/4"
715104T	Textile hose R7 5/32"	mt 10	racc 1/4"
715154T	Textile hose R7 5/32"	mt 15	racc 1/4"
715204T	Textile hose R7 5/32"	mt 20	racc 1/4"
Conn. Steel-Hose 5/32"-Press. max: 200 Bar (Psi 2900)			

Spécifications techniques

Technical-constructive features:

inner core in polyamide, polyester textile reinforcement and exterior covering in antiabrasion micro perforated polyurethane for the conduction of air and compatible gases. These hoses are not able to dissipate electrostatic charges that may build up in case non-conductive fluids are conveyed.

Application:

these R7 hoses series have been created for medium pressure conduction of polyols, solvents, paints and compatible gases.

Working temperature:

from -40°C to +100°C From -40°F to +212°F

Max. working temperature of air, water and water-based fluids is + 95°C (+203°F).

Vacuum rating:

0,93 bar; 700 mm Hg

Specifications:

meet or exceed SAE J517 sez. SAE 100R7 - ISO 3949 standards.